


IR MOTORIZED VF DOME CAMERA

DI-340IP5MVF



1/3" CMOS Sensor

4 Mega-Pixel

True Day & Night (IR Cut Removable)

H.265 (HEVC) Compression

0 Lux (IR On) Min. Illumination

ONVIF

True WDR / BLC / HLC

3D Noise Reduction

Motion Detection and Privacy Masking

Analytics Support

3.3-12mm Motorized Lens with Auto-Focus

25m IR Illumination

PoE Support

IP 66 Protection

Specifications

Camera	Video	Model	I4-340IP5MVF
		Image Sensor	1/3" CMOS
		Effective Pixels	2688x1520
		Electronic Shutter	1/25s ~ 1/100000s
		Frame Rate	Standard: 1-25/30 (True-WDR), HFR*: 1-50/60 (Max. 1080P & D-WDR)
		Day & Night	ICR
		Min. Illumination	0lux (IR ON)
	Audio	Audio compression	G.711A/G.711U
		Communication	One-way Audio
	Image Processing	Image Settings	AWB, AGC Adjustable Exposure Mode (Auto)
		Image Enhancement	Sharpness, Saturation, Brightness & Contrast Adjustable
		Noise Reduction	3D-DNR
		Image Orientation	Mirror/Flip
		Privacy Zone	Yes
	Compression	Motion Detection	Yes
		Analytics	Pro Level
		Video Compression	H.265 / H.264 / MJPEG (Sub-Stream Only)
		Resolution	4MP(2560x1440), 3MP(2048x1536), 1080P, 720P, D1, CIF, 480x240
		Multi-Stream	4MP / 3MP / 1920x1080 / 1280x720 / D1 / CIF / 480x240 (1~25/30FPS / 1~50/60FPS with HFR*)
		Bit rate	64Kbps ~ 7Mbps@H.265 / 128Kbps ~ 9Mbps@H.264
		Encode Mode	VBR/CBR
		Image Quality	Five levels under VBR; Free adjustment under CBR

Housing	IR Distance	25m (2 High Power IR LED)
	Lens	3.3-12mm Motorized with Auto Focus
	Iris	Fixed Iris
	Lens Mount	Φ14 mount
	Protection Rate	Water Proof: IP66
	Bracket	3-Axis Wall Bracket
	Dimensions	Ø120mm×100mm
Connectivity	Weight(gross)	400g
	Network	RJ45 (+PoE)
	Power	DC Socket
	Analog Video Output	CVBS (BNC)
	Mic Connectivity	1Ch Input
	SD Card	No
	RS485	No
Network	Alarm	No
	Remote Monitoring	IE Browsing, CMS Software, Provision Cam2 Mobile App
	User Access	Supports simultaneous monitoring for up to 4 users with multi-stream real time transmission
	Network Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1X, Multicast, QoS
	ONVIF	Yes
	Ethernet	100Mbps
	PoE	Yes
Others	Power Supply	DC12V/~280mA / PoE/~4W
	Work Environment	-30 C ~50 C, 10%~90% Humidity

*HFR (High Frame Rate) must be supported by the NVR in order to work properly.

